

Invitation to tender text:

Manufacture of water-bound coverings in accordance with DIN 18035 T 5.

The topsoil is to be verified as flat surface with minimum slope required in accordance with DIN.

--- m² 15 cm support layer in accordance with DIN 18035 from GELSENROT® PORLITH 0-32

Install profile-related and compact statically stable with suitable roller.

--- m² 6 cm layer dynamic from PORLITH 0-15

Supply free to construction site with test certificate, in accordance with DIN 18035 Part 5, and apply in moist status uniformly and profile-related and compact. Through levelling it is to be verified that slope is in accordance with DIN.

--- m² 4 cm surface course from GELSENROT® 0-8; Colour.....

Developed for the special requirements of water-bound path covers with good water permeability, frost resisting, quality-monitored, with test certificate in accordance with DIN 18035 Part 5, supply free to construction site and apply in the moist status at a minimum thickness of 4 cm (compacted status) uniformly and profile-related, and compact. Through levelling it is to be verified that slope is in accordance with DIN.

All specifications are to be documented through a test certificate for the testing of the material equivalence by an independent testing institute. The billing is implemented by delivery note.

Manufacturer:

GELSENROT® Spezialbaustoffe GmbH
Engelbertstraße 16
45892 Gelsenkirchen
Tel.: 0209/70008-0
Fax: 0209/70008-99